



Technical Specification

		Maximus Click	Maximus Click Herringbone
Description		Rigid core SPC with click locking system	Rigid core SPC with click locking system
Thickness	EN ISO 24337	6.00 mm	5.00 mm
Wearlayer	EN ISO 24340	0.55 mm	0.55 mm
Wearlayer PUR coating		Scratchmaster® top layer	Scratchmaster® top layer
Weight per sqm	EN ISO 23997	ca. 9820 g/m ²	ca. 9700 g/m ²
Locking System		Unilin's Unizip® click technology	Unilin's Unizip® click technology
Classification	EN ISO 10874	23 Domestic Heavy - 34 Commercial Very Heavy	23 Domestic Heavy - 34 Commercial Very Heavy

Performance

Reaction to fire	EN 13501-1	Bfl-S1	Bfl-S1
Slip resistance	EN 13893	DS	DS
Slip restraint (dynamic coefficient of friction)	DIN 51130	R10	R10
Thermal conductivity	EN 12664	0.048 (W/m.K)	0.165 (W/m.K)
Thermal resistance R value	EN 12664	0.031 (m ² .K)/W	0.031 (m ² .K)/W
Underfloor heating	EN ISO 12524	Yes, max. 27°C	Yes, max. 27°C
Electrostatic performance	EN 1815	< 2 kV	< 2 kV
Residual indentation	EN ISO 24343-1	< 0.1 mm	< 0.1 mm
Dimensional stability	EN ISO 23999	≤ 0.15%	≤ 0.25%
Curling	EN ISO 23999	pass	pass
Castor chair resistance	EN ISO 4918	pass, Type W	≥ 25000 Cycles, no damage
Colour fastness	EN ISO 105-B02	> 6	> 6
Impact sound insulation	EN ISO 717-2	20dB (ΔLw)	8dB (ΔLw)
Chemical / Stain resistance	EN ISO 26987	pass	pass
Abrasion resistance	EN ISO 660-1	class T	class T
Indoor AIR quality - French VOC regulation	ISO 16000	Greenguard GOLD - Floorscore - A+	Greenguard GOLD - Floorscore - A+
Content of pentachlorophenol		PCP under detection limit	PCP under detection limit
Formaldehyde emissions (28 days test)	EN ISO 717-1	NA HCHO (has not been added)	NA HCHO (has not been added)
Phthalate free		Yes, biobased	Yes, biobased
CE marking	EN 14041:2011		

Packaging

Size and packaging wood	EN ISO 24342	178x1213mm - 8 planks/carton = 1.725 m ² /carton	-
Size and packaging wood XL planks	EN ISO 24342	235x1500mm - 4 planks/carton = 1.426 m ² /carton	-
Size and packaging wood XL planks	EN ISO 24342	225x1500mm - 4 planks/carton = 1.350 m ² /carton	-
Size and packaging stone	EN ISO 24342	298x603mm - 8 tiles/carton = 1.440 m ² /carton	-
Size and packaging stone XL tiles	EN ISO 24342	450x907mm - 4 tiles/carton = 1.633 m ² /carton	-
Size and packaging Herringbone	EN ISO 24342	-	145x743mm - 14 planks/carton = 1.509 m ² /carton

Warranty

Warranty	25 years Residential - 15 years Commercial	25 years Residential - 15 years Commercial
----------	--	--

The technical data is correct at the time of printing. v2 - 06/2021

